

# Water Deionizer System™

Maximize battery performance with pure water from the tap



Hard water in your water supply may be causing poor battery performance. Metallic impurities in water can affect cell voltages and increase self discharge, resulting in shortened battery run time and reduced battery life. The traditional method to avoid water impurities is to use distilled water, an expensive and inconvenient proposition. Using deionized water is a simple and effective way to maximize battery life.

## Easy to use

- Comes with everything you need to make pure water from the tap
- Operates at full-line pressure to dispense pure water directly from the deionizer
- Quick cartridge replacement requires no tools
- 20-ft output hose allows maximum watering flexibility and convenience
- Optional Watering Gun lets you fill a battery directly from the deionizer

## High capacity

- Cartridge is rated for 600 gallons, 2300 litres, of pure water\*

\* Capacity varies with purity of incoming water.

See table on reverse side

## Exclusive battery-operated purity light

- Dual color light indication signals when it's time to change the cartridge
  - Green light means water quality is OK
  - Red light means it is time to change cartridge
  - No light means batteries need to be changed
- Includes 2 D-cell batteries that will last for 2 years
- No need to mount near AC power source

# Water Deionizer System™

Convenient and cost-effective, the Water Deionizer System™ enables you to maintain battery capacity and long life

## Easy installation

A mounting plate with hose hanger is provided for easy installation. The cartridge has standard hose fittings and connects in seconds to the input and output hoses with quick-connect couplings. No plumber or maintenance department is required. Cartridge replacement takes just seconds – and disposal is easy because cartridge contents are non-toxic.

## Pressurized system

Unlike some lab-type systems, the PS-300 cartridge takes full-line pressure up to 80 psi, 5.5 bar. So the water flow is fast enough to use directly with the Watering Gun.

## Low cost

Cartridges are available for a fraction of the cost of distilled water, enabling battery users to produce their own pure water for less money than it would cost to buy it.

## Exclusive battery-operated purity light

A conductivity meter continuously monitors the output water and signals when it is time to change the cartridge. Battery operation eliminates the need for AC power, making system mounting flexible and convenient. Two standard D-cell batteries are included and will last for 2 years.

## High capacity

A single cartridge will produce an average of 600 gallons, 2300 litres, of purified water. The amount will vary with the quality of the incoming tap water – from as much as 1,500 gallons, 5700 litres, to as little as 250, 1000 litres. Most battery manufacturers recommend that water should have no greater than 50 parts per million total dissolved solids in order to get full battery life.

## Watering gun available

An optional Battery Watering Gun is available, enabling a battery to be filled directly from the deionizer.



### Specifications

<b>Flow Rate</b>	<b>0.5 gpm (2.0 lpm)</b> <b>(with provided restrictor)</b>
<b>Purity Light Power Source (included)</b>	<b>2 D-Cell Batteries</b>
<b>Life Estimate</b>	<b>2 Years</b>
<b>Purity Light Setting</b>	<b>50 ppm total dissolved solids</b>
<b>Dimensions</b>	<b>Mounting plate</b> <b>44" x 6" (1115mm x 155mm)</b> <b>Disposable Cartridge</b> <b>27" x 4.5" (690mm x 123mm)</b>
<b>Hose Dimensions</b>	<b>3/8" x 10' (9.5mm x 3m) (input)</b> <b>3/8" x 20' (9.5mm x 6m) (output)</b> <b>Garden thread hose fittings</b>

	Purity of Incoming Tap Water		Output of a Single Deionizer Cartridge	
	TDS (PPM)	Conductivity (µS/cm)	Gallons	Liters
Good	20	30.0	3,600	13,627
	50	75.0	1,440	5,451
	75	112.5	960	3,634
Average	100	150.0	720	2,725
	125	187.5	576	2,180
	150	225.0	480	1,817
Poor	200	300.0	360	1,363
	250	375.0	288	1,090
	300	450.0	240	908



[www.phlsci.com](http://www.phlsci.com)

**Philadelphia Scientific Americas**  
207 Progress Drive, Montgomeryville, PA, 18936 USA  
P: +1 (0) 215 616 0390 F: +1 (0) 215 616 0500

**Philadelphia Scientific EMEA**  
188 Oxford Grove, Bolton, BL1 3BH, UK  
P: +44 (0) 1204 467777 F: +44 (0) 1204 493300

**Philadelphia Scientific Asia Pacific**  
2/17 Norman Street, Peakhurst, NSW, 2210, Australia  
P: +61 (0) 2 8004 2447 F: +61 (0) 2 9012 0383